

COIN CELLS


Lithium

Non-rechargeable, 3 Volt lithium/manganese dioxide coin cells in a wide range of industry recognised sizes with an option of pcb mount versions on capacities of 150mAh and above. All types feature a high capacity/size ratio, long shelf life due to low self discharge rates and level voltage discharge characteristics.

- ◆ 3 volt lithium coin cells
- ◆ Long shelf life, low self discharge
- ◆ Industry recognised sizes
- ◆ PCB mount option

Conventional Cells

Standard form of cells. Suitable for use in applications where convenient battery replacement is required.

	Nominal Capacity (mAh)	Dimensions (mm)		Manf. Part No.	anglia Order Code
		Dia. (A)	Height (B)		
	25	12.5	1.6	CR1216	730030
	30	10.0	2.5	CR1025	730020
	38	12.5	2.0	CR1220	730040
	48	12.5	2.5	CR1225	730050
	50	16.0	1.6	CR1616	730060
	68	16.0	2.0	CR1620	730070
	80	20.0	1.6	CR2016	730090
	125	16.0	3.2	CR1632	730080
	150	20.0	2.5	CR2025	730100
	150	23.0	2.0	CR2320	730120
	190	23.0	2.5	CR2325	730130
	200	20.0	3.2	CR2032	730110
	300	24.5	3.0	CR2430	730140
	540	24.5	5.0	CR2450N	730150
	950	24.5	7.7	CR2477N	730160

Dimensions (mm)




COIN CELL HOLDERS & CLIPS
see pages 25-27


PCB Mount Cells

Cells terminated with pcb pins. Choice of orientation. Ideal for memory back-up applications.


Horizontal

	Nominal Capacity (mAh)	Dimensions (mm)				Manf. Part No.	anglia Order Code
		A	B	C	D		
	150	20.2	2.5	4.85	15.2	CR2025RH	730100H
	190	23.2	2.5	4.85	17.8	CR2325RH	730130H
	200	20.2	3.2	5.45	15.2	CR2032RH	730110H
	200	20.2	3.2	5.45	17.8	CR2032RH1	730111H
	300	24.7	3.0	5.45	17.8	CR2430RH	730140H
	540	24.7	5.0	7.35	17.8	CR2450NRH	730150H
	950	24.7	7.7	10.05	17.8	CR2477NRH	730160H


Dimensions (mm)




Footprint




Vertical

	Nominal Capacity (mAh)	Dimensions (mm)				Manf. Part No.	anglia Order Code
		A	B	C	D		
	150	20.0	2.5	21.0	2.8	CR2025RV	730100V
	190	23.0	2.5	24.0	2.8	CR2325RV	730130V
	200	20.0	3.2	21.0	3.5	CR2032RV	730110V
	300	24.5	3.0	25.5	3.3	CR2430RV	730140V
	540	24.5	5.0	25.5	5.3	CR2450NRV	730150V
	950	24.5	7.7	25.5	8.0	CR2477NRV	730160V



Footprint



Renata Zinc Air and Silver Oxide cells also available to special order