




DIAC



Breakover Voltage (V)			Device No. & anglia Order Code	Breakover Voltage Symmetry dV max. (V)	Breakover Current I _{BO} max. (μA)	dV between 0 and 10mA min. (V)	Package
min.	nom.	max.					
28	32	36	Taped DB3	±3	100	5	DO35
			DB3A	±3	100	5	DO41
			DB3AS	±3	100	5	DO41 mod / A405

SIDAC



SHINDENGEN

Off State Voltage (V)	Breakover Voltage (V)		Device No. & anglia Order code	Effective Current I _T (A)	Off State Current I _{DRM} max. (μA)	Breakover Current I _{BO} max. (mA)	Hold Current I _H typ. (mA)	Colour Code	Package
	min.	max.							
40	45	60	K1V5	1	10	0.5	50	Red	AX10
	55	65	K1V6					Gold	
70	77	95	K1V8	1	10	0.5	50	Silver	AX10
90	95	113	K1V10	1	10	0.5	50	Orange	AX10
	104	118	K1V11					Blue	
	110	125	K1V12					Green	
90	95	113	K1V(A)10	1	10	0.5	50	Orange	AX06
	104	118	K1V(A)11					Blue	
	110	125	K1V(A)12					Green	
115	125	150	K1V14	1	10	0.5	30	Violet	AX10
	145	170	K1V16						
115	125	150	K1V(A)14	1	10	0.5	50	Violet	AX06
	145	170	K1V(A)16						
150	165	200	K1V18	1	10	0.5	50	Violet	AX10
180	200	230	K1V22	1	10	0.5	20	Yellow	AX10
	220	250	K1V24						
	240	270	K1V26						
	200	230	K1V22(W)				50		
	220	250	K1V24(W)						
	240	265	K1V26(W)						
200	230	K1V33(W)	50						
270	320	360		K1V34(W)					
	340	380		K1V36(W)					
	360	400		K1V38(W)					

Package Dimensions (mm)

