Product Change Notification

PCN26-6-Rev A_ELUM series – Yellow/Green LED change

C&K
2 rue Berthollet - B.P. 359 F-39105 Dole Cedex - France
Tel :+33 (0)3 84 72 81 12 www.ckswitches.com

Document subject to change without prior notice

Document revision

Revision	Date	Description	Author
A	March, 17th, 2026	Creation	Lina Guan

Summary

1. Purpose 4
2. Overview 4
3. Impact of Change and Qualification 6
4. Part numbers affected 6
5. Date of application 6
6. Conditions of application 7
7. Customer qualification 7
8. Acknowledgement 7
9. Support 7

1. Purpose

C&K has been notified by its supplier, the end of production of several LEDs.

This discontinuation from KINGBRIGHT (supplier A), without direct replacement proposal, is leading C&K to modify its ELUM lighted series by using the closest replacement from the market.

C&K switches selected ORMSEN (supplier B) to replace the bicolor Yellow/Green LED in its products.

The impact for our customers will be some differences in the lighting characteristics.

2. Overview

2.1 Change definition

Supplier A: KINGBRIGHT manufacturer of the bicolor Yellow-Green LED, reference **WP967-CKC8.**

Selection Guide

Part No.	Dice	Lens Type	Iv (mcd) [2] @ 20mA		Viewing Angle [1]
			Min.	Typ.	2θ1/2
WP967-CKC8	Yellow (GaAsP/GaP)	WHITE DIFFUSED	2.6	10	60°
	Super Bright Green (GaP)		2.6	20	

Electrical / Optical Characteristics at TA=25°C

Symbol	Parameter	Device	Typ.	Max.	Units	Test Conditions
λpeak	Peak Wavelength	Yellow Super Bright Green	590 565		nm	IF=20mA
λD [1]	Dominant Wavelength	Yellow Super Bright Green	588 568		nm	IF=20mA
Δλ1/2	Spectral Line Half-width	Yellow Super Bright Green	35 30		nm	IF=20mA
C	Capacitance	Yellow Super Bright Green	20 15		pF	VF=0V;f=1MHz
VF [2]	Forward Voltage	Yellow Super Bright Green	2.1 2.2	2.5 2.5	V	IF=20mA

Absolute Maximum Ratings at TA=25°C

Parameter	Yellow	Super Bright Green	Units
Power dissipation	75	62.5	mW
DC Forward Current	30	25	mA
Peak Forward Current [1]	140	140	mA
Operating / Storage Temperature	-40°C To +85°C		
Lead Solder Temperature [2]	260°C For 3 Seconds		
Lead Solder Temperature [3]	260°C For 5 Seconds		

Supplier B: ORMSEN manufacturer of the bicolor Yellow-Green LED, reference **OS-RGY234-2W-TR1(CK)**.
The color, luminous intensity, the viewing angle and ratings of new Yellow-Green LED are somewhat different to the existing one.

Device Selection Guide

Chip Materials	Emitted Color	Resin Color
GaP	Green	White Diffused
GaP	Yellow	

Absolute Maximum Ratings (Ta=25℃)

Parameter	Symbol		Rating	Unit
Continuous Forward Current	I_F	G/Y	30	mA
Peak Forward Current (Duty 1/10 @ 1KHZ)	I_{FP}	G/Y	75	mA
Reverse Voltage	V_R	G/Y	1.1	V
Power Dissipation	P_d	G/Y	75	mW
Operating Temperature	T_{opr}	G/Y	-40 ~ +85	℃
Storage Temperature	Tstg	G/Y	-40 ~ +85	℃
Soldering Temperature	T_{sol}	G/Y	260 ℃ for 5 sec.	

Electro-Optical Characteristics (Ta=25℃)

Parameter	Symbol		Min	Typ	Max	Unit	Condition
Luminous Intensity	I_v	G	8	25	-----	mcd	IF=20mA
		Y	8	25	-----		
Viewing Angle	$2\theta_{1/2}$	G/Y	-----	90	-----	deg	IF=20mA
Peak Wavelength	λ_p	G	-----	575	-----	nm	IF=20mA
		Y		595			
Dominant Wavelength	λ_d	G	-----	570	-----	nm	IF=20mA
		Y		590			
Spectrum Radiation Bandwidth	$\Delta\lambda$	G	-----	20	-----	nm	IF=20mA
		Y		20			
Forward Voltage	V_F	G/Y	1.7	2.0	2.4	V	IF=20mA
Reverse Current	I_R	G/Y	-----	-----	10	μA	VR=1.1V

3. Impact of Change and Qualification

3.1 Impact of Change:

There is no change to the form, fit and function of the switch.

3.2 Qualification method:

As the modification only affects the LED and its integration in the switch, the qualification focuses solely on the LED performance:

- Luminosity, Chromaticity Coordinates
- Endurance test
- Climatic tests
- Salt spray test
- Soldering test

The qualification has been completed in C&K, test report is available upon request.

Samples for qualification are already available upon request.

4. Part numbers affected

All item featuring **Yellow/Green LED** are affected by this notification.

Material N°	Material Description
ELUMEESAQ8C12	SWITCH ELUMEESAQ8C12
ELUMEESAQ8C22	SWITCH ELUMEESAQ8C22
ELUMEETHQ8C12	SWITCH ELUMEETHQ8C12
ELUMEETHQ8C22	SWITCH ELUMEETHQ8C22
ELUMOASAQ8C12	SWITCH ELUMOASAQ8C12
ELUMOASAQ8C22	SWITCH ELUMOASAQ8C22
ELUMOATHQ8C12	SWITCH ELUMOATHQ8C12
ELUMOATHQ8C22	SWITCH ELUMOATHQ8C22

5. Date of application

Effective immediately. There is no remaining stock of LEDs WP967-CKC8 from Supplier A.
All finished products are now manufactured using LEDs OS-RGY234-2W-TR1(CK) from Supplier B.

6. Conditions of application

Pricing and stock handling policy:

- Pricing: Any pricing and other sales conditions remain valid.
- Stock handling: no obsolescence and no specification modification are applied on any P/N. No return or scrap for obsolescence will be accepted

7. Customer qualification

C&K recommends its customers to carry on the lighting compatibility check and qualifications they feel necessary to make sure that they will be ready at the date of application. Switching characteristics are not modified in order to minimize the customer impact and make easier the modification acceptation.

8. Acknowledgement

We kindly ask you to acknowledge receipt of this information to your sales representative so C&K can start planning the phase in – out process accordingly.

Please forward your requirements in terms of samples & qualification files at the following email address: lguan@Littelfuse.com

9. Support

For any question, please contact your sales representative