

Sandall Road Wisbech PE13 2PS UK

Tel: +44 (0)1945 47 47 47 Fax: +44 (0)1945 47 48 49

Update to tooling

PCN Number	PCNN01029
Publication Date	15/05/2025
Effectivity Date	Immediate
Change Summary	Updated tooling

## Dear Customer,

Anglia have been advised by our supplier that the tooling for 621029 has been updated with immediate effect, this is due to the old tooling being beyond its serviceable life. The supplier advised they have also taken this opportunity to revise the mouldings to improve the efficiency and yield of the production process. The revised parts have some minor dimensional and cosmetic appearance changes but the form, fit, and function of the part remains the same.

Attached below are the old and new data sheets for comparison purposes.

Anglia operates a strict FIFO system in our Distribution Centre facility; therefore, it may take time for this change to filter through to customer deliveries of the part number(s).

Please make the relevant person(s) in your organisation aware of this change.

Yours Sincerely

Anglia

Anglia Part Numbers
Affected
621029

## DC SOCKETS

A range of low cost commercial grade DC connectors. Black moulded bodies house switched contacts with connection by pcb terminations. Rated 12V, 1A. Choice of size.




Size


2.5mm

anglia Order Code 621029








 $\square$ : TERMINAL NO.




P.C.B Layout




















## **SPECIFICATION**

1.Rating : DC 20V 4A; 2.Contact resistance: ≤30mΩ;

3.Insulation resistance: ≥100MΩ (DC500V); 4.Withstand voltage: 500VAC ; 5.Insertion and extraction force: 3-30N; 6.life test: 5,000 cycles;

7. Operation temperature range:  $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ ; 8. Preservative temperature range:  $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ ;

## Recommended PCB Layout (PCB TOLERANCE $\pm 0.05$ )

NO.	DESCRIPTION		QTY	MATERIAL	REMARK
1	Housing		1	PBT	
2	Cover		1	PBT	
3	Center pin	1	1	Brass	CuSn/Nickel platin
4	Center pin terminal	1	1	Brass t=0.40	Tin plating
(5)	Tip spring	2	1	Phosphor bronze t=0.30	Tin plating
6	Shunt terminal	3	1	Brass t=0.5	Tin plating

RoHS Compliant

Part Number: 621029		Angle:	$\boxed{\hspace{1.5cm}}$
Title: DC Power Jack			
all dimensions in mm	Tol. (unless stated)		.x = ±0.30