



## Product/Process Change Notice - PCN 15\_0178 Rev. B

Analog Devices, Inc. Three Technology Way Norwood, Massachusetts 02062-9106

This notice is to inform you of a change that will be made to certain ADI products (see Appendix A) that you may have purchased in the last 2 years. **Any inquiries or requests with this PCN (additional data or samples) must be sent to ADI within 30 days of publication date.** ADI contact information is listed below.

*Note: Revised fields are indicated by a red field name. See Appendix B for revision history.*

**PCN Title:** ADV7619 Settings and Related Data Sheet Specification updates  
**Publication Date:** 09-Nov-2015  
**Effectivity Date:** 09-Nov-2015 *(the earliest date that a customer could expect to receive changed material)*

### Revision Description:

Additional I2C write added for modes > 170MHz.

### Description Of Change

#### 1. Configuration Setting Change:

The ADV7619 recommended setting scripts for video resolutions with a pixel clock of over 170MHz have been updated to incorporate the following writes:

```
; Added write to IO Map, 98 00 19 ; Set VID_STD  
; Added write to IO Map, 98 01 05 ; Prim_Mode =101b HDMI-Comp  
; Added write to IO Map, 98 DD 00 ; Default value  
; Added write to IO Map, 98 E7 04 ; ADI Required Write  
; Added write to DPLL Map, 4C DB 80 ; ADI Required Write
```

The ADV7619 settings are outlined in the ADV7619 Required Settings document and the recommended settings script file available from Engineer Zone.

#### 2. Datasheet Addition:

An additional clock duty cycle specification for video resolutions with a pixel clock of over 170MHz was added to the ADV7619 datasheet.

Specification: LLC Mark-Space Ratio

Time Descriptor: t9:t10

Description: For input video resolutions with a pixel clock frequency > 170 MHz

Minimum Spec: 40:60 % duty cycle

Maximum Spec: 60:40 % duty cycle

The ADV7619 datasheet is available from the ADV7619 product page on the Analog Devices website.

### Reason For Change

In conjunction with the silicon, the ADV7619 recommended I2C settings are a critical element of an overall stable solution. This change is being made to improve the timing-related stability of the I2C settings at certain combinations of material, voltage and temperature. There is no change of material associated with this PCN.

The modification changes the clock path employed for video resolutions with a pixel clock of over 170MHz. It has been confirmed that the new clock path resolves the timing-related stability issues observed with the old clock path at certain combinations of material, voltage and temperature. The new clock path has a slightly higher level of clock duty cycle distortion, please see the above change description for the clock duty cycle specification.

### Impact of the change (positive or negative) on fit, form, function & reliability

The following are the impacts of this change:

1. Application Software Change

Customers must add the new configuration settings into their application software to guarantee the most robust performance of ADV7619

2. Duty Cycle Ratio

Customers must analyse their application hardware to ensure that their setup and hold timing margin is still sufficient given the increased clock duty cycle.

**Product Identification** *(this section will describe how to identify the changed material)*

This change is effective from date code 1539.

**Summary of Supporting Information**

The changes described above are reflected in the ADV7619 Rev. D data sheet, the ADV7619 Required Settings document Rev 1.8 and the ADV7619 recommended settings script file Rev 1.9.

**Supporting Documents**      None

**For questions on this PCN, please send an email to the regional contacts below or contact your local ADI sales representatives.**

**Americas:**    PCN\_Americas@analog.com

**Europe:**    PCN\_Europe@analog.com

**Japan:**      PCN\_Japan@analog.com

**Rest of Asia:**    PCN\_ROA@analog.com

**Appendix A - Affected ADI Models**

**Existing Parts - Product Family / Model Number (2)**

ADV7619 / ADV7619KSVZ

ADV7619 / ADV7619KSVZ-P

**Appendix B - Revision History**

<b>Rev</b>	<b>Publish Date</b>	<b>Effectivity Date</b>	<b>Rev Description</b>
Rev. -	22-Sep-2015	22-Sep-2015	Initial Release
Rev. A	09-Oct-2015	09-Oct-2015	Update the pixel clock frequency from which the new configuration settings must be applied (170MHz). Update effectivity date code.
Rev. B	09-Nov-2015	09-Nov-2015	Additional I2C write added for modes > 170MHz.

Analog Devices, Inc.

DocId:3488 Parent DocId:None Layout Rev:7