

Change limits:

Slope Current (Accuracy vs Temperature) T_{min} to T_{max}

T grade	FROM 0.98 TO 0.96 mA Min
---------	--------------------------

Intercept Voltage

B grade	FROM 0.95 TO 0.93 mV Min
---------	--------------------------

T grade	FROM 0.95 TO 0.93 mV Min
---------	--------------------------

Total Absolute DC Accuracy

V_{in} = +/-1mV to +/-100mV

B grade	FROM 0.9 TO 1.2 dB Max
---------	------------------------

T grade	FROM 0.9 TO 1.2 dB Max
---------	------------------------

Over Temperature (T_{min} to T_{max})

B grade	FROM 1.7 TO 2.0 dB Max
---------	------------------------

T grade	FROM 1.8 TO 2.0 dB Max
---------	------------------------

Over Supply Range (V_s = 4.5 to 7.5V)

B grade	FROM 1.0 TO 1.5 dB Max
---------	------------------------

T grade	FROM 1.0 TO 1.5 dB Max
---------	------------------------

Using Attenuator (V_{in} = +/-10mV to +/-1V)

Over Temperature (T_{min} to T_{max})

B grade	FROM 2.0 TO 2.2 dB Max
---------	------------------------

T grade	FROM 2.0 TO 2.2 dB Max
---------	------------------------

Logarithmic Output

Intercept, Dual AD640s, freq <= 1 MHz

B grade	FROM -89.6 TO -90.0 dBm Min
---------	-----------------------------

T grade	FROM -89.6 TO -90.0 dBm Min
---------	-----------------------------