

## ADG5412 Family Data Sheet changes

This document highlights the performance changes on the data sheets of the ADG5412 family of Analog Switch and Multiplexers.

There are 4 generics included in this document and they are as follows:

1. ADG5412/ADG5413
2. ADG5404
3. ADG5436

The tables below show a datasheet specification comparison of the current datasheet specification to the updated version for each generic. The changed specifications are highlighted in red font.

## 1. ADG5412/ADG5413 SPECIFICATION CHANGES FROM Rev. C to Rev. D

Parameter	Rev. C			Rev. D			Unit
	+25°C	-40°C to +85°C	-40°C to +125°C	+25°C	-40°C to +85°C	-40°C to +125°C	
LEAKAGE CURRENTS							
Source Off Leakage, $I_s$ (Off)	±0.05			±0.05			nA typ
	±0.25	±0.75	±3.5	±0.25	±0.75	±6	nA max
Drain Off Leakage, $I_b$ (Off)	±0.05			±0.05			nA typ
	±0.25	±0.75	±3.5	±0.25	±0.75	±6	nA max
Channel On Leakage, $I_b$ (On), $I_s$ (On)	±0.1			±0.1			nA typ
	±0.4	±2	±12	±0.4	±2	±12	nA max

## 2. ADG5404 SPECIFICATION CHANGES FROM Rev. A to Rev. B

Parameter	Rev. A			Rev. B			Unit
	+25°C	-40°C to +85°C	-40°C to +125°C	+25°C	-40°C to +85°C	-40°C to +125°C	
LEAKAGE CURRENTS							
Source Off Leakage, $I_s$ (Off)	±0.05			±0.05			nA typ
	±0.25	±0.75	±3.5	±0.25	±0.75	±6	nA max
Drain Off Leakage, $I_b$ (Off)	±0.1			±0.1			nA typ
	±0.4	±2	±12	±0.4	±2	±16	nA max
Channel On Leakage, $I_b$ (On), $I_s$ (On)	±0.1			±0.1			nA typ
	±0.4	±2	±12	±0.4	±2	±16	nA max

## 3. ADG5436 SPECIFICATION CHANGES FROM Rev. B to Rev. C

Parameter	Rev. B			Rev. C			Unit
	+25°C	-40°C to +85°C	-40°C to +125°C	+25°C	-40°C to +85°C	-40°C to +125°C	
LEAKAGE CURRENTS							
Source Off Leakage, $I_s$ (Off)	±0.05			±0.05			nA typ
	±0.25	±0.75	±3.5	±0.25	±0.75	±6	nA max
Drain Off Leakage, $I_b$ (Off)	±0.1			±0.1			nA typ
	±0.4	±2	±12	±0.4	±2	±12	nA max
Channel On Leakage, $I_b$ (On), $I_s$ (On)	±0.1			±0.1			nA typ
	±0.4	±2	±12	±0.4	±2	±12	nA max