



Product/Process Change Notice - PCN 19_0080 Rev. A

Analog Devices, Inc. Three Technology Way Norwood, Massachusetts 02062-9106

This notice is to inform you of a change that will be made to certain ADI products (see Appendix A) that you may have purchased in the last 2 years. **Any inquiries or requests with this PCN (additional data or samples) must be sent to ADI within 30 days of publication date.** ADI contact information is listed below.

Note: Revised fields are indicated by a red field name. See Appendix B for revision history.

PCN Title: ADIS1649X Layout Change

Publication Date: 26-Aug-2019

Effectivity Date: 28-Sep-2019 *(the earliest date that a customer could expect to receive changed material)*

Revision Description:

Revised to clarify reason for change.

Description Of Change:

Add voltage supervisory circuitry to limit the in-rush current of the module during turn on, which requires a layout change and additional components.

Reason For Change:

This PCN covers an ADIS16490, ADIS16495 and ADIS16497 IMU design change which brings the observable in-rush current during power-up initialization sequence to 300 mA. During the initial power on sequence, a nominal peak of 500mA will still be experienced during the ramp of the VDD supply which is unchanged and follows: $I = C \times dVDD/dt$, where $C = 46\mu F$. While there is no reliability concern for the existing IMU design, this change helps ensure that customers' IMU power supplies are not overstressed during IMU power-up.

The peak current consumption at power-up for existing ADIS16490, ADIS16495 and ADIS16497 IMUs is 3.2A at VDD = +3.6V. A plot of the VDD current with respect to time is a triangular profile with a total duration of less than 100 μs . Note that a lower VDD will result in a peak current level that is less than 3.2A.

Impact of the change (positive or negative) on fit, form, function & reliability:

Removes the most stressing current demand at turn on.

Product Identification *(this section will describe how to identify the changed material)*

Earliest Possible date that will include the change is DC1932

Summary of Supporting Information:

Qualification will be performed per Industry Standard Test Methods. See attached Qualification Plan.

Supporting Documents

Attachment 1: Type: Qualification Plan

ADI_PCN_19_0080_Rev_A_PCN19_0080Attachment.docx

For questions on this PCN, please send an email to the regional contacts below or contact your local ADI sales representatives.

Americas:
PCN_Americas@analog.com

Europe:
PCN_Europe@analog.com

Japan:
PCN_Japan@analog.com

Rest of Asia:
PCN_ROA@analog.com

Appendix A - Affected ADI Models

Existing Parts - Product Family / Model Number (8)

ADIS16490 / ADIS16490BMLZ	ADIS16495 / AD24495	ADIS16495 / ADIS16495-1BMLZ	ADIS16495 / ADIS16495-2BMLZ	ADIS16495 / ADIS16495-3BMLZ
ADIS16497 / ADIS16497-1BMLZ	ADIS16497 / ADIS16497-2BMLZ	ADIS16497 / ADIS16497-3BMLZ		

Appendix B - Revision History

Rev	Publish Date	Effectivity Date	Rev Description
Rev. -	26-Jun-2019	28-Sep-2019	Initial Release
Rev. A	26-Aug-2019	28-Sep-2019	Revised to clarify reason for change.

Analog Devices, Inc.

DocId:6818 Parent DocId:None Layout Rev:7