



Product/Process Change Notice - PCN 23_0010 Rev. -

Analog Devices, Inc. One Analog Way, Wilmington, MA 01887, USA

This notice is to inform you of a change that will be made to certain ADI products (see Appendix A) that you may have purchased in the last 2 years. **Any inquiries or requests with this PCN (additional data or samples) must be sent to ADI within 30 days of publication date.** ADI contact information is listed below.

PCN Title:	ADG5208F, ADG5209F, ADG5243F, ADG5248F, ADG5249F Datasheet Specification Change
Publication Date:	06-Mar-2023
Effectivity Date:	08-Jun-2023 <i>(the earliest date that a customer could expect to receive changed material)</i>
Revision Description:	Initial Release

Description Of Change:

Changes to the datasheet specification and/or Test conditions regarding the following parameters:

- 1) On Resistance
- 2) On-Resistance Match Between Channels
- 3) On Resistance Flatness
- 4) Power Requirements

The following product datasheets are affected: ADG5208F, ADG5209F, ADG5243F, ADG5248F, ADG5249F.
Please see attachment for full change details

Reason For Change:

To accurately reflect the capability of the devices.

Impact of the change (positive or negative) on fit, form, function & reliability:

There will be no impact on form, fit, function, quality or reliability of any of the products.

Product Identification *(this section will describe how to identify the changed material)*

The change over date code will be advised in a later revision of this PCN

Summary of Supporting Information:

These specification changes will be outlined in
Rev.B of the ADG5208F/ADG5209F datasheet
Rev.B of the ADG5248F/ADG5249F datasheet
Rev.C of the ADG5243F datasheet

Supporting Documents

Attachment 1: Type: Datasheet Specification Comparison

[ADI_PCN_23_0010_Rev_-ADG5208F Family On resistance Power Supply PCN D...](#)

Note: If applicable, the device material declaration will be updated due to material change.

ADI Contact Information:

For questions on this PCN, please send an email to the regional contacts below or contact your local ADI sales representatives.

Americas:

Europe:

Japan:

Rest of Asia:

Appendix A - Affected ADI Models:

Added Parts On This Revision - Product Family / Model Number (15)

ADG5208F / ADG5208FBCPZ-RL7	ADG5208F / ADG5208FBRUZ	ADG5208F / ADG5208FBRUZ-RL7	ADG5209F / ADG5209FBCPZ-RL7	ADG5209F / ADG5209FBRUZ
ADG5209F / ADG5209FBRUZ-RL7	ADG5243F / ADG5243FBCPZ-RL7	ADG5243F / ADG5243FBRUZ	ADG5243F / ADG5243FBRUZ-RL7	ADG5248F / ADG5248FBCPZ-RL7
ADG5248F / ADG5248FBRUZ	ADG5248F / ADG5248FBRUZ-RL7	ADG5249F / ADG5249FBCPZ-RL7	ADG5249F / ADG5249FBRUZ	ADG5249F / ADG5249FBRUZ-RL7



ADG5208F, ADG5209F, ADG5243F, ADG5248F, ADG5249F PCN 23_0010

Datasheet Comparison

ADG5208F ADG5209F ±15 V DUAL SUPPLY

$V_{DD} = 15\text{ V} \pm 10\%$, $V_{SS} = -15\text{ V} \pm 10\%$, $GND = 0\text{ V}$, $C_{DECOUPLING} = 0.1\ \mu\text{F}$, unless otherwise noted.

Table 1.

Parameter	+25°C	-40°C to +85°C	-40°C to +125°C	Unit	Test Conditions/Comments	
ANALOG SWITCH						
Analog Signal Range			V_{DD} to V_{SS}	V	$V_{DD} = +13.5\text{ V}$, $V_{SS} = -13.5\text{ V}$,	
On Resistance, R_{ON}	250			Ω typ	$V_S = \pm 10\text{ V}$, $I_S = -1\text{ mA}$	
	270	335	395	Ω max		
	250			Ω typ	$V_S = \pm 9\text{ V}$, $I_S = -1\text{ mA}$	
	270	335	395	Ω max		
On-Resistance Match Between Channels, ΔR_{ON}	2.5			Ω typ	$V_S = \pm 10\text{ V}$, $I_S = -1\text{ mA}$	
	6 -> 8	12 -> 14	13 -> 15	Ω max		
	2.5			Ω typ	$V_S = \pm 9\text{ V}$, $I_S = -1\text{ mA}$	
	6 -> 8	12 -> 14	13 -> 15	Ω max		
On-Resistance Flatness, $R_{FLAT(ON)}$	6.5			Ω typ	$V_S = \pm 10\text{ V}$, $I_S = -1\text{ mA}$	
	8 -> 8.5	9 -> 9.5	9 -> 9.5	Ω max		
	1.5			Ω typ	$V_S = \pm 9\text{ V}$, $I_S = -1\text{ mA}$	
	3.5	4	4	Ω max		
POWER REQUIREMENTS						
Normal Mode						
I_{DD}	1.3			mA typ	$V_{DD} = +16.5\text{ V}$; $V_{SS} = -16.5\text{ V}$; $GND = 0\text{ V}$; digital inputs = 0 V, 5 V, or V_{DD}	
	2 -> 2.15		2 -> 2.15	mA max		
I_{GND}	0.75			mA typ		
	1.25 -> 1.4		1.25 -> 1.4	mA max		
I_{SS}	0.65			mA typ		
	0.8 -> 0.95		0.85 -> 1	mA max		
Fault Mode						
I_{DD}	1.6			mA typ		
	2.2 -> 2.5		2.3 -> 2.6	ma max		
I_{GND}	0.9			ma typ		
	1.6 -> 1.8		1.7 -> 1.9	ma max		
I_{SS}	0.65			ma typ		
	1.0 -> 1.2		1.1 -> 1.3	mA max		

Rev. A

[Document Feedback](#)

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700 ©2015–2016 Analog Devices, Inc. All rights reserved.
[Technical Support](#) www.analog.com

ADG5208F ADG5209F ±20 V DUAL SUPPLY

$V_{DD} = 20\text{ V} \pm 10\%$, $V_{SS} = -20\text{ V} \pm 10\%$, $GND = 0\text{ V}$, $C_{DECOUPLING} = 0.1\text{ }\mu\text{F}$, unless otherwise noted.

Table 2.

Parameter	+25°C	-40°C to +85°C	-40°C to +125°C	Unit	Test Conditions/Comments	
ANALOG SWITCH						
Analog Signal Range			V_{DD} to V_{SS}	V	$V_{DD} = +18\text{ V}$, $V_{SS} = -18\text{ V}$	
On Resistance, R_{ON}	260			Ω typ	$V_S = \pm 15\text{ V}$, $I_S = -1\text{ mA}$	
	280 -> 290	345 -> 355	405 -> 415	Ω max		
On-Resistance Match Between Channels, ΔR_{ON}	250			Ω typ	$V_S = \pm 13.5\text{ V}$, $I_S = -1\text{ mA}$	
	270	335	395	Ω max		
	2.5			Ω typ		
On-Resistance Flatness, $R_{FLAT(ON)}$	6 -> 8	12 -> 14	13 -> 15	Ω max	$V_S = \pm 15\text{ V}$, $I_S = -1\text{ mA}$	
	2.5			Ω typ		
	6 -> 8	12 -> 14	13 -> 15	Ω max		
	12.5			Ω typ		
	14	15	15	Ω max	$V_S = \pm 15\text{ V}$, $I_S = -1\text{ mA}$	
	1.5			Ω typ		
	3.5	4	4	Ω max		
POWER REQUIREMENTS						
Normal Mode						
I_{DD}	1.3			mA typ	$V_{DD} = +22\text{ V}$; $V_{SS} = -22\text{ V}$; $GND = 0\text{ V}$; digital inputs = 0 V, 5 V, or V_{DD}	
	2 -> 2.15		2 -> 2.15	mA max		
I_{GND}	0.75			mA typ		
	1.25 -> 1.4		1.25 -> 1.4	mA max		
I_{SS}	0.65			mA typ		
	0.8 -> 0.95		0.85 -> 1	mA max		
Fault Mode						
I_{DD}	1.6			mA typ		
	2.2 -> 2.5		2.3 -> 2.6	mA max		
I_{GND}	0.9			mA typ		
	1.6 -> 1.8		1.7 -> 1.9	mA max		
I_{SS}	0.65			mA typ		
	1.0 -> 1.2		1.1 -> 1.3	mA max		

Data Sheet Comparison

ADG5208F ADG5209F 12 V SINGLE SUPPLY

$V_{DD} = 12\text{ V} \pm 10\%$, $V_{SS} = 0\text{ V}$, $GND = 0\text{ V}$, $C_{DECOUPLING} = 0.1\text{ }\mu\text{F}$, unless otherwise noted.

Table 3.

Parameter	+25°C	-40°C to +85°C	-40°C to +125°C	Unit	Test Conditions/Comments
ANALOG SWITCH					
Analog Signal Range			0 V to V_{DD}	V	$V_{DD} = 10.8\text{ V}$, $V_{SS} = 0\text{ V}$
On Resistance, R_{ON}	630			Ω typ	$V_S = 0\text{ V to }10\text{ V}$, $I_S = -1\text{ mA} \rightarrow$ $V_S = 0\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$
	690	710	730	Ω max	
	270			Ω typ	$V_S = 3.5\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$
	290	355	410	Ω max	
On-Resistance Match Between Channels, ΔR_{ON}	6			Ω typ	$V_S = 0\text{ V to }10\text{ V}$, $I_S = -1\text{ mA} \rightarrow$ $V_S = 0\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$
	17 \rightarrow 19	19 \rightarrow 21	19 \rightarrow 21	Ω max	
	3			Ω typ	$V_S = 3.5\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$
	6.5 \rightarrow 8	11 \rightarrow 12.5	12 \rightarrow 13.5	Ω max	
On-Resistance Flatness, $R_{FLAT(ON)}$	380			Ω typ	$V_S = 0\text{ V to }10\text{ V}$, $I_S = -1\text{ mA} \rightarrow$ $V_S = 0\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$
	440	460	460	Ω max	
	25			Ω typ	$V_S = 3.5\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$
	27 \rightarrow 28	28 \rightarrow 29	28 \rightarrow 29	Ω max	
POWER REQUIREMENTS					
Normal Mode					
I_{DD}	1.3			mA typ	$V_{DD} = 13.2\text{ V}$; $V_{SS} = 0\text{ V}$; $GND = 0\text{ V}$; digital inputs = 0 V, 5 V, or V_{DD}
	2 \rightarrow 2.15		2 \rightarrow 2.15	mA max	
I_{GND}	0.75			mA typ	
	1.4		1.4	mA max	
I_{SS}	0.5			mA typ	
	0.65 \rightarrow 0.95		0.7 \rightarrow 1	mA max	
Fault Mode					
I_{DD}	1.6			mA typ	$V_S = \pm 55\text{ V}$
	2.2 \rightarrow 2.5		2.3 \rightarrow 2.6	mA max	
I_{GND}	0.9			mA typ	
	1.6 \rightarrow 1.8		1.7 \rightarrow 1.9	mA max	
I_{SS}	0.65			mA typ	Digital inputs = 5 V
	1.0 \rightarrow 1.2		1.1 \rightarrow 1.3	mA max	$V_S = \pm 55\text{ V}$, $V_D = 0\text{ V}$

ADG5208F ADG5209F 36 V SINGLE SUPPLY

$V_{DD} = 36\text{ V} \pm 10\%$, $V_{SS} = 0\text{ V}$, $GND = 0\text{ V}$, $C_{DECOUPLING} = 0.1\text{ }\mu\text{F}$, unless otherwise noted.

Table 4.

Parameter	+25°C	-40°C to +85°C	-40°C to +125°C	Unit	Test Conditions/Comments	
ANALOG SWITCH						
Analog Signal Range			0 V to V_{DD}	V	$V_{DD} = 32.4\text{ V}$, $V_{SS} = 0\text{ V}$	
On Resistance, R_{ON}	310			Ω typ	$V_S = 0\text{ V to }30\text{ V}$, $I_S = -1\text{ mA}$	
	335	415	480	Ω max		
	250			Ω typ		
	270	335	395	Ω max		
On-Resistance Match Between Channels, ΔR_{ON}	3			Ω typ	$V_S = 0\text{ V to }30\text{ V}$, $I_S = -1\text{ mA}$	
	7 -> 8	16 -> 17	18 -> 19	Ω max		
On-Resistance Flatness, $R_{FLAT(ON)}$	3			Ω typ	$V_S = 4.5\text{ V to }28\text{ V}$, $I_S = -1\text{ mA}$	
	6.5 -> 8	11 -> 12.5	12 -> 13.5	Ω max		
	62			Ω typ	$V_S = 0\text{ V to }30\text{ V}$, $I_S = -1\text{ mA}$	
	70	85	100	Ω max		
	1.5			Ω typ		
	3.5 -> 4.5	4 -> 5	4 -> 5	Ω max	$V_S = 4.5\text{ V to }28\text{ V}$, $I_S = -1\text{ mA}$	
POWER REQUIREMENTS						
Normal Mode						
I_{DD}	1.3			mA typ	$V_{DD} = 39.6\text{ V}$; $V_{SS} = 0\text{ V}$; $GND = 0\text{ V}$; digital inputs = 0V, 5V, or V_{DD}	
	2 -> 2.15		2 -> 2.15	mA max		
I_{GND}	0.75			mA typ		
I_{SS}	1.4		1.4	mA max		
	0.5			mA typ		
	0.65 -> 0.95		0.7 -> 1	mA max		
Fault Mode						
I_{DD}	1.6			mA typ		$V_S = +55\text{ V}$, -40 V
	2.2 -> 2.5		2.3 -> 2.6	mA max		
I_{GND}	0.9			mA typ		
	1.6 -> 1.8		1.7 -> 1.9	mA max		
I_{SS}	0.65			mA typ		
	1.0 -> 1.2		1.1 -> 1.3	mA max		

Data Sheet Comparison

ADG5243F ±15 V DUAL SUPPLY

$V_{DD} = 15\text{ V} \pm 10\%$, $V_{SS} = -15\text{ V} \pm 10\%$, $GND = 0\text{ V}$, $C_{DECOUPLING} = 0.1\text{ }\mu\text{F}$, unless otherwise noted.

Table 5.

Parameter	+25°C	-40°C to +85°C	-40°C to +125°C	Unit	Test Conditions/Comments	
ANALOG SWITCH						
Analog Signal Range			V_{DD} to V_{SS}	V	$V_{DD} = +13.5\text{ V}$, $V_{SS} = -13.5\text{ V}$	
On Resistance, R_{ON}	250			Ω typ	$V_S = \pm 10\text{ V}$, $I_S = -1\text{ mA}$	
	270	335	395	Ω max		
	250			Ω typ	$V_S = \pm 9\text{ V}$, $I_S = -1\text{ mA}$	
	270	335	395	Ω max		
On-Resistance Match Between Channels, ΔR_{ON}	1			Ω typ	$V_S = \pm 10\text{ V}$, $I_S = -1\text{ mA}$	
	4 -> 8	5 -> 9	5 -> 9	Ω max		
	1			Ω typ	$V_S = \pm 9\text{ V}$, $I_S = -1\text{ mA}$	
	4 -> 8	5 -> 9	5 -> 9	Ω max		
On-Resistance Flatness, $R_{FLAT(ON)}$	7			Ω typ	$V_{DD} = +15\text{ V}$, $V_{SS} = -15\text{ V}$, $V_S = \pm 10\text{ V}$, $I_S = -1\text{ mA}$	
	8.5	9.5	9.5	Ω max		
	1.5			Ω typ	$V_{DD} = +15\text{ V}$, $V_{SS} = -15\text{ V}$, $V_S = \pm 9\text{ V}$, $I_S = -1\text{ mA}$	
	3.5	4.5	4.5	Ω max		
POWER REQUIREMENTS						
Normal Mode						
I_{DD}	1.3			mA typ	$V_{DD} = \text{POSFV} = +16.5\text{ V}$, $V_{SS} = \text{NEGFV} = -16.5\text{ V}$ $GND = 0\text{ V}$, digital inputs = 0 V, 5 V, or V_{DD}	
I_{POSFV}	0.15			mA typ		
$I_{DD} + I_{\text{POSFV}}$	2 -> 2.15		2.1 -> 2.25	mA max		
I_{GND}	0.75			mA typ		
	1.25 -> 1.4		1.4 -> 1.55	mA max		
I_{SS}	0.65			mA typ		
I_{NEGFV}	0.2			mA typ		
$I_{SS} + I_{\text{NEGFV}}$	0.95		1.0	mA max		
Fault Mode						
I_{DD}	1.4			mA typ		
I_{POSFV}	0.2			mA typ		
$I_{DD} + I_{\text{POSFV}}$	2.5		2.8	mA max		
I_{GND}	0.9			mA typ		
	1.8		1.9	mA max		
I_{SS}	0.55			mA typ		
I_{NEGFV}	0.2			mA typ		
$I_{SS} + I_{\text{NEGFV}}$	1.0 -> 1.2		1.1 -> 1.3	mA max		

ADG5243F ±20 V DUAL SUPPLY

$V_{DD} = 20\text{ V} \pm 10\%$, $V_{SS} = -20\text{ V} \pm 10\%$, $GND = 0\text{ V}$, $C_{DECOUPLING} = 0.1\text{ }\mu\text{F}$, unless otherwise noted.

Table 6.

Parameter	+25°C	-40°C to +85°C	-40°C to +125°C	Unit	Test Conditions/Comments	
ANALOG SWITCH						
ANALOG SWITCH					$V_{DD} = +18\text{ V}$, $V_{SS} = -18\text{ V}$	
Analog Signal Range			V_{DD} to V_{SS}	V		
On Resistance, R_{ON}	270			Ω typ	$V_S = \pm 15\text{ V}$, $I_S = -1\text{ mA}$	
	290	355	410	Ω max		
	250			Ω typ	$V_S = \pm 13.5\text{ V}$, $I_S = -1\text{ mA}$	
	270	335	395	Ω max		
On-Resistance Match Between Channels, ΔR_{ON}	1			Ω typ	$V_S = \pm 15\text{ V}$, $I_S = -1\text{ mA}$	
	4->8	5->9	5->9	Ω max		
	1			Ω typ	$V_S = \pm 13.5\text{ V}$, $I_S = -1\text{ mA}$	
	4->8	5->9	5->9	Ω max		
On-Resistance Flatness, $R_{FLAT(ON)}$	27			Ω typ	$V_{DD} = +20\text{ V}$, $V_{SS} = -20\text{ V}$; $V_S = \pm 15\text{ V}$, $I_S = -1\text{ mA}$	
	29.5	29.5	29.5	Ω max		
	5			Ω typ	$V_{DD} = +20\text{ V}$, $V_{SS} = -20\text{ V}$; $V_S = \pm 13.5\text{ V}$, $I_S = -1\text{ mA}$	
	6.5	8.5	8.5	Ω max		
POWER REQUIREMENTS						
Normal Mode						
I_{DD}	1.3			mA typ	$V_{DD} = \text{POSFV} = +22\text{ V}$, $V_{SS} = \text{NEGFV} = -22\text{ V}$, $GND = 0\text{ V}$, digital inputs = 0 V, 5 V, or V_{DD}	
I_{POSFV}	0.15			mA typ		
$I_{DD} + I_{\text{POSFV}}$	2->2.15		2.1->2.25	mA max		
I_{GND}	0.75			mA typ		
	1.25->1.4		1.4->1.55	mA max		
I_{SS}	0.65			mA typ		
I_{NEGFV}	0.2			mA typ		
$I_{SS} + I_{\text{NEGFV}}$	1.0		1.0	mA max		
Fault Mode						
I_{DD}	1.4			mA typ		$V_S = \pm 55\text{ V}$, all channels in fault
I_{POSFV}	0.2			mA typ		
$I_{DD} + I_{\text{POSFV}}$	2.5		2.8	mA max		
I_{GND}	0.9			mA typ		
	1.8		1.9	mA max		
I_{SS}	0.55			mA typ		
I_{NEGFV}	0.2			mA typ		
$I_{SS} + I_{\text{NEGFV}}$	1.0->1.2		1.1->1.3	mA max		
V_{DD}/V_{SS}			± 5	V min	$GND = 0\text{ V}$	
			± 22	V max	$GND = 0\text{ V}$	

Data Sheet Comparison

ADG5243F 12 V SINGLE SUPPLY

$V_{DD} = 12\text{ V} \pm 10\%$, $V_{SS} = 0\text{ V}$, $GND = 0\text{ V}$, $C_{DECOUPLING} = 0.1\text{ }\mu\text{F}$, unless otherwise noted.

Table 7.

Parameter	+25°C	-40°C to +85°C	-40°C to +125°C	Unit	Test Conditions/Comments	
ANALOG SWITCH						
Analog Signal Range			0 V to V_{DD}	V	$V_{DD} = 10.8\text{ V}$, $V_{SS} = 0\text{ V}$	
On Resistance, R_{ON}	630			Ω typ	$V_S = 0\text{ V to }10\text{ V}$, $I_S = -1\text{ mA} \rightarrow$ $V_S = 0\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$	
	690	710	730	Ω max		
	270			Ω typ	$V_S = 3.5\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$	
	290	355	410	Ω max		
On-Resistance Match Between Channels, ΔR_{ON}	6			Ω typ	$V_S = 0\text{ V to }10\text{ V}$, $I_S = -1\text{ mA} \rightarrow$ $V_S = 0\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$	
	19	19	19	Ω max		
	1			Ω typ	$V_S = 3.5\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$	
	5 -> 8	5 -> 8	5 -> 8	Ω max		
On-Resistance Flatness, $R_{FLAT(ON)}$	380			Ω typ	$V_S = 0\text{ V to }10\text{ V}$, $I_S = -1\text{ mA} \rightarrow$ $V_S = 0\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$	
	440	460	460	Ω max		
	25			Ω typ	$V_S = 3.5\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$	
	27 -> 28	28 -> 29	28 -> 29	Ω max		
POWER REQUIREMENTS						
Normal Mode						
I_{DD}	1.3			mA typ	$V_{DD} = \text{POSFV} = 13.2\text{ V}$, $V_{SS} = \text{NEGFV} = 0\text{ V}$, $GND = 0\text{ V}$, digital inputs = 0 V, 5 V, or V_{DD}	
I_{POSFV}	0.15			mA typ		
$I_{DD} + I_{\text{POSFV}}$	2 -> 2.15		2.1 -> 2.25	mA max		
I_{GND}	0.75			mA typ		
	1.4		1.5	mA max		
I_{SS}	0.55			mA typ		
I_{NEGFV}	0.2			mA typ		
$I_{SS} + I_{\text{NEGFV}}$	0.95		1.0	mA max		
Fault Mode						
I_{DD}	1.4			mA typ		$V_S = \pm 55\text{ V}$, all channels in fault
I_{POSFV}	0.2			mA typ		
$I_{DD} + I_{\text{POSFV}}$	2.5		2.8	mA max		
I_{GND}	0.9			mA typ		
	1.8		1.9	mA max		
I_{SS}	0.55			mA typ	Digital inputs = 5 V	
I_{NEGFV}	0.2			mA typ		
$I_{SS} + I_{\text{NEGFV}}$	1.0 -> 1.2		1.1 -> 1.3	mA max	$V_S = \pm 55\text{ V}$, $V_D = 0\text{ V}$	

ADG5243F 36 V SINGLE SUPPLY

$V_{DD} = 36\text{ V} \pm 10\%$, $V_{SS} = 0\text{ V}$, $GND = 0\text{ V}$, $C_{DECOUPLING} = 0.1\text{ }\mu\text{F}$, unless otherwise noted.

Table 8.

Parameter	+25°C	-40°C to +85°C	-40°C to +125°C	Unit	Test Conditions/Comments	
ANALOG SWITCH						
Analog Signal Range			0 V to V_{DD}	V	$V_{DD} = 32.4\text{ V}$, $V_{SS} = 0\text{ V}$	
On Resistance, R_{ON}	310			Ω typ	$V_S = 0\text{ V to }30\text{ V}$, $I_S = -1\text{ mA}$	
	335	415	480	Ω max		
	250			Ω typ	$V_S = 4.5\text{ V to }28\text{ V}$, $I_S = -1\text{ mA}$	
	270	335	395	Ω max		
On-Resistance Match Between Channels, ΔR_{ON}	3			Ω typ	$V_S = 0\text{ V to }30\text{ V}$, $I_S = -1\text{ mA}$	
	7 -> 8	16 -> 17	18 -> 19	Ω max		
	3			Ω typ	$V_S = 4.5\text{ V to }28\text{ V}$, $I_S = -1\text{ mA}$	
	6.5 -> 8	11 -> 12.5	12 -> 13.5	Ω max		
On-Resistance Flatness, $R_{FLAT(ON)}$	62			Ω typ	$V_S = 0\text{ V to }30\text{ V}$, $I_S = -1\text{ mA}$	
	70	85	100	Ω max		
	1.5			Ω typ	$V_S = 4.5\text{ V to }28\text{ V}$, $I_S = -1\text{ mA}$	
	3.5 -> 4.5	4 -> 5	4 -> 5	Ω max		
POWER REQUIREMENTS						
Normal Mode						
I_{DD}	1.3			mA typ	$V_{DD} = POSFV = 39.6\text{ V}$, $V_{SS} = NEGFV = 0\text{ V}$, $GND = 0\text{ V}$, digital inputs = 0 V, 5 V, or V_{DD} $V_S = +55\text{ V}$, -40 V , all channels in fault	
I_{POSFV}	0.15			mA typ		
$I_{DD} + I_{POSFV}$	2 -> 2.15		2.1 -> 2.25	mA max		
I_{GND}	0.75			mA typ		
	1.4		1.5	mA max		
I_{SS}	0.55			mA typ		
I_{NEGFV}	0.2			mA typ		
$I_{SS} + I_{NEGFV}$	0.95		1.0	mA max		
Fault Mode						
I_{DD}	1.4			mA typ		
I_{POSFV}	0.2			mA typ		
$I_{DD} + I_{POSFV}$	2.5		2.8	mA max		
I_{GND}	0.9			mA typ		
	1.8		1.9	mA max		
I_{SS}	0.55			mA typ		
I_{NEGFV}	0.2			mA typ		
$I_{SS} + I_{NEGFV}$	1.0 -> 1.2		1.1 -> 1.3	mA max		

Data Sheet Comparison

ADG5248F ADG5249F ±15 V DUAL SUPPLY

$V_{DD} = 15\text{ V} \pm 10\%$, $V_{SS} = -15\text{ V} \pm 10\%$, $GND = 0\text{ V}$, $C_{DECOUPLING} = 0.1\ \mu\text{F}$, unless otherwise noted.

Table 9.

Parameter	+25°C	-40°C to +85°C	-40°C to +125°C	Unit	Test Conditions/Comments
ANALOG SWITCH					
Analog Signal Range			V_{DD} to V_{SS}	V	$V_{DD} = +13.5\text{ V}$, $V_{SS} = -13.5\text{ V}$
On Resistance, R_{ON}	250			Ω typ	$V_S = \pm 10\text{ V}$, $I_S = -1\text{ mA}$
	270	335	395	Ω max	
	250			Ω typ	$V_S = \pm 9\text{ V}$, $I_S = -1\text{ mA}$
	270	335	395	Ω max	
On-Resistance Match Between Channels, ΔR_{ON}	2.5			Ω typ	$V_S = \pm 10\text{ V}$, $I_S = -1\text{ mA}$
	6 -> 8	12 -> 14	13 -> 15	Ω max	
	2.5			Ω typ	$V_S = \pm 9\text{ V}$, $I_S = -1\text{ mA}$
	6 -> 8	12 -> 14	13 -> 15	Ω max	
On-Resistance Flatness, $R_{FLAT(ON)}$	6.5			Ω typ	$V_S = \pm 10\text{ V}$, $I_S = -1\text{ mA}$
	8 -> 8.5	9 -> 9.5	9 -> 9.5	Ω max	
	1.5			Ω typ	$V_S = \pm 9\text{ V}$, $I_S = -1\text{ mA}$
	3.5	4	4	Ω max	
POWER REQUIREMENTS					
Normal Mode					
I_{DD}	1.15			mA typ	$V_{DD} = POSFV = +16.5\text{ V}$; $V_{SS} = NEGfV = -16.5\text{ V}$; $GND = 0\text{ V}$; digital inputs = 0 V, 5 V, or V_{DD}
I_{POSFV}	0.15			mA typ	
$I_{DD} + I_{POSFV}$	2 -> 2.15		2 -> 2.15	mA max	
I_{GND}	0.75			mA typ	
	1.25 -> 1.4		1.25 -> 1.4	mA max	
I_{SS}	0.45			mA typ	
I_{NEGfV}	0.2			mA typ	
$I_{SS} + I_{NEGfV}$	0.8 -> 0.95		0.85 -> 1	mA max	
Fault Mode					
I_{DD}	1.4			mA typ	$V_S = \pm 55\text{ V}$
I_{POSFV}	0.2			mA typ	
$I_{DD} + I_{POSFV}$	2.2 -> 2.5		2.3 -> 2.6	mA max	
I_{GND}	0.9			mA typ	
	1.6 -> 1.8		1.7 -> 1.9	mA max	
I_{SS}	0.45			mA typ	
I_{NEGfV}	0.2			mA typ	
$I_{SS} + I_{NEGfV}$	1.0 -> 1.2		1.1 -> 1.3	mA max	
V_{DD}/V_{SS}			± 5	V min	$GND = 0\text{ V}$
			± 22	V max	$GND = 0\text{ V}$

ADG5248F ADG5249F ±20 V DUAL SUPPLY

$V_{DD} = 20\text{ V} \pm 10\%$, $V_{SS} = -20\text{ V} \pm 10\%$, $GND = 0\text{ V}$, $C_{DECOUPLING} = 0.1\text{ }\mu\text{F}$, unless otherwise noted.

Table 10.

Parameter	+25°C	-40°C to +85°C	-40°C to +125°C	Unit	Test Conditions/Comments	
ANALOG SWITCH						
Analog Signal Range			V_{DD} to V_{SS}	V	$V_{DD} = +18\text{ V}$, $V_{SS} = -18\text{ V}$	
On Resistance, R_{ON}	260			Ω typ	$V_S = \pm 15\text{ V}$, $I_S = -1\text{ mA}$	
	280 -> 290	345 -> 355	405 -> 415	Ω max		
	250			Ω typ	$V_S = \pm 13.5\text{ V}$, $I_S = -1\text{ mA}$	
	270	335	395	Ω max		
On-Resistance Match Between Channels, ΔR_{ON}	2.5			Ω typ	$V_S = \pm 15\text{ V}$, $I_S = -1\text{ mA}$	
	6 -> 8	12 -> 14	13 -> 15	Ω max		
	2.5			Ω typ	$V_S = \pm 13.5\text{ V}$, $I_S = -1\text{ mA}$	
	6 -> 8	12 -> 14	13 -> 15	Ω max		
On-Resistance Flatness, $R_{FLAT(ON)}$	12.5			Ω typ	$V_S = \pm 15\text{ V}$, $I_S = -1\text{ mA}$	
	14	15	15	Ω max		
	1.5			Ω typ	$V_S = \pm 13.5\text{ V}$, $I_S = -1\text{ mA}$	
	3.5	4	4	Ω max		
POWER REQUIREMENTS						
Normal Mode						
I_{DD}	1.15			mA typ	$V_{DD} = \text{POSFV} = +22\text{ V}$; $V_{SS} = \text{NEGFV} = -22\text{ V}$; digital inputs = 0 V, 5 V, or V_{DD} $V_S = \pm 55\text{ V}$	
I_{POSFV}	0.15			mA typ		
$I_{DD} + I_{\text{POSFV}}$	2 -> 2.15		2 -> 2.15	mA max		
I_{GND}	0.75			mA typ		
	1.25 -> 1.4		1.25 -> 1.4	mA max		
I_{SS}	0.45			mA typ		
I_{NEGFV}	0.2			mA typ		
$I_{SS} + I_{\text{NEGFV}}$	0.8 -> 0.95		0.85 -> 1	mA max		
Fault Mode						
I_{DD}	1.4			mA typ		
I_{POSFV}	0.2			mA typ		
$I_{DD} + I_{\text{POSFV}}$	2.2 -> 2.5		2.3 -> 2.6	mA max		
I_{GND}	0.9			mA typ		
	1.6 -> 1.8		1.7 -> 1.9	mA max		
I_{SS}	0.45			mA typ		
I_{NEGFV}	0.2			mA typ		
$I_{SS} + I_{\text{NEGFV}}$	1.0 -> 1.2		1.1 -> 1.3	mA max		

Data Sheet Comparison

ADG5248F ADG5249F 12 V SINGLE SUPPLY

$V_{DD} = 12\text{ V} \pm 10\%$, $V_{SS} = 0\text{ V}$, $GND = 0\text{ V}$, $C_{DECOUPLING} = 0.1\text{ }\mu\text{F}$, unless otherwise noted.

Table 11.

Parameter	+25°C	-40°C to +85°C	-40°C to +125°C	Unit	Test Conditions/Comments
ANALOG SWITCH					
Analog Signal Range			0 V to V_{DD}	V	$V_{DD} = 10.8\text{ V}$, $V_{SS} = 0\text{ V}$
On Resistance, R_{ON}	630			Ω typ	$V_S = 0\text{ V to }10\text{ V}$, $I_S = -1\text{ mA} \rightarrow$ $V_S = 0\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$
	690	710	730	Ω max	
	270			Ω typ	$V_S = 3.5\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$
	290	355	410	Ω max	
On-Resistance Match Between Channels, ΔR_{ON}	6			Ω typ	$V_S = 0\text{ V to }10\text{ V}$, $I_S = -1\text{ mA} \rightarrow$ $V_S = 0\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$
	17 -> 19	19 -> 21	19 -> 21	Ω max	
	3			Ω typ	$V_S = 3.5\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$
	6.5 -> 8	11 -> 12.5	12 -> 13.5	Ω max	
On-Resistance Flatness, $R_{FLAT(ON)}$	380			Ω typ	$V_S = 0\text{ V to }10\text{ V}$, $I_S = -1\text{ mA} \rightarrow$ $V_S = 0\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$
	440	460	460	Ω max	
	25			Ω typ	$V_S = 3.5\text{ V to }8.5\text{ V}$, $I_S = -1\text{ mA}$
	27 -> 28	28 -> 29	28 -> 29	Ω max	
POWER REQUIREMENTS					
Normal Mode					
I_{DD}	1.15			mA typ	$V_{DD} = 13.2\text{ V}$; $V_{SS} = 0\text{ V}$; digital inputs = 0 V, 5 V, or V_{DD}
I_{POSFV}	0.15			mA typ	
$I_{DD} + I_{POSFV}$	2 -> 2.15		2 -> 2.15	mA max	
I_{GND}	0.75			mA typ	
	1.4		1.4	mA max	
I_{SS}	0.3			mA typ	
I_{NEGFV}	0.2			mA typ	
$I_{SS} + I_{NEGFV}$	0.65 -> 0.95		0.7 -> 1	mA max	
Fault Mode					
I_{DD}	1.4			mA typ	$V_S = \pm 55\text{ V}$
I_{POSFV}	0.2			mA typ	
$I_{DD} + I_{POSFV}$	2.2 -> 2.5		2.3 -> 2.6	mA max	
I_{GND}	0.9			mA typ	
	1.6 -> 1.8		1.7 -> 1.9	mA max	
I_{SS}	0.45			mA typ	Digital inputs = 5 V
I_{NEGFV}	0.2			mA typ	
$I_{SS} + I_{NEGFV}$	1.0 -> 1.2		1.1 -> 1.3	mA max	$V_S = \pm 55\text{ V}$, $V_D = 0\text{ V}$

ADG5248F ADG5249F 36 V SINGLE SUPPLY

$V_{DD} = 36\text{ V} \pm 10\%$, $V_{SS} = 0\text{ V}$, $GND = 0\text{ V}$, $C_{DECOUPLING} = 0.1\text{ }\mu\text{F}$, unless otherwise noted.

Table 12.

Parameter	+25°C	-40°C to +85°C	-40°C to +125°C	Unit	Test Conditions/Comments	
ANALOG SWITCH						
Analog Signal Range			0 V to V_{DD}	V	$V_{DD} = 32.4\text{ V}$, $V_{SS} = 0\text{ V}$	
On Resistance, R_{ON}	310			Ω typ	$V_S = 0\text{ V to }30\text{ V}$, $I_S = -1\text{ mA}$	
	335	415	480	Ω max		
	250			Ω typ	$V_S = 4.5\text{ V to }28\text{ V}$, $I_S = -1\text{ mA}$	
	270	335	395	Ω max		
On-Resistance Match Between Channels, ΔR_{ON}	3			Ω typ	$V_S = 0\text{ V to }30\text{ V}$, $I_S = -1\text{ mA}$	
	7 -> 8	16 -> 17	18 -> 19	Ω max		
On-Resistance Flatness, $R_{FLAT(ON)}$	3			Ω typ	$V_S = 4.5\text{ V to }28\text{ V}$, $I_S = -1\text{ mA}$	
	6.5 -> 8	11 -> 12.5	12 -> 13.5	Ω max		
	62			Ω typ	$V_S = 0\text{ V to }30\text{ V}$, $I_S = -1\text{ mA}$	
	70	85	100	Ω max		
	1.5			Ω typ	$V_S = 4.5\text{ V to }28\text{ V}$, $I_S = -1\text{ mA}$	
3.5 -> 4.5	4 -> 5	4 -> 5	Ω max			
POWER REQUIREMENTS						
Normal Mode						
I_{DD}	1.15			mA typ	$V_{DD} = 39.6\text{ V}$; $V_{SS} = 0\text{ V}$; digital inputs = 0 V, 5 V, or V_{DD}	
I_{POSFV}	0.15			mA typ		
$I_{DD} + I_{POSFV}$	2 -> 2.15		2 -> 2.15	mA max		
I_{GND}	0.75			mA typ		
	1.4		1.4	mA max		
I_{SS}	0.3			mA typ		
I_{NEGFV}	0.2			mA typ		
$I_{SS} + I_{NEGFV}$	0.65 -> 0.95		0.7 -> 1	mA max		
Fault Mode						
I_{DD}	1.4			mA typ		$V_S = +55\text{ V}$, -40 V
I_{POSFV}	0.2			mA typ		
$I_{DD} + I_{POSFV}$	2.2 -> 2.5		2.3 -> 2.6	mA max		
I_{GND}	0.9			mA typ		
	1.6 -> 1.8		1.7 -> 1.9	mA max		
I_{SS}	0.45			mA typ		
I_{NEGFV}	0.2			mA typ		
$I_{SS} + I_{NEGFV}$	1.0 -> 1.2		1.1 -> 1.3	mA max		
V_{DD}			8	V min	$GND = 0\text{ V}$	
			44	V max	$GND = 0\text{ V}$	

Appendix B - Revision History:

Rev	Publish Date	Effectivity Date	Rev Description
Rev. -	06-Mar-2023	08-Jun-2023	Initial Release