



Product Service

CERTIFICATE

No. B 101520 0002 Rev. 00

Model(s): 0717, 0717-1 and 0717-1S Series
(see table 1 for details)

Parameters:	Rated voltage:	250V~
	Rated frequency:	50/60Hz
	Rated current:	10A
	Protection class:	I
	Standard Sheet:	C14
	Maximum pin temperature:	Cold conditions
Remark:	The integrated fuse holder complied with EN 60127-6:2014.	

Table 1: model details

	0717-	x1-	x2	x3	x4	x5
x1	Denotes Enclosure Design Blank : Fitted With 1 Fuse And With Screw-On Enclosure 1: Fitted With 1 Fuse And With Snap-In Enclosure 1S: Fitted With 1 Fuse And With Snap-In Enclosure Which May Incorporated With A Switch					
x2	Denotes Way of Mounting C: Screw-on (Countersink Ear, for x1 = Blank only) F: Screw-on (Flat Ear, for x1 = Blank only) P: Snap-in (for x1 = 1 or 1S)					
x3	Denotes Terminal Type W: Q.D/Solder Tab, 6.3 × 0.8 mm Q: Q.D/Solder Tab, 4.8 × 0.8 mm L: Solder Tab, 2.8 × 0.8 mm S: Solder Tab, 2.5 × 0.8 mm SG: Solder Tab, 2.5 × 0.8 mm (EMI)					
x4	Denotes Vender Code for Marketing Purpose Can be 0-9, A-Z or Blank					
x5	Denotes Vender Code for Marketing Purpose Can be 0-9, A-Z or Blank					

Tested according to: EN 60320-1:2015

Production 004524

Facility(ies):

ZERTIFIKAT ◆ CERTIFICATE ◆ 認 證 證 書 ◆ CERTIFICADO ◆ CERTIFICAT