

Comparison report

Prepared by Meg Yu
Checked by Zoe Chiang
Approved by Stanley Lin
Issued date at Mar.07.2016
Reversion for A

***** The copyright of document and business secret belong to TSC, and no copies should be made without any permission *****

Subject: Remove parameter Trr from datasheet

Remark : take S1xL for example

old datasheet version

| MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted) | | | | | | | | | | | |
|---|------------------------------------|--------------|------|------|------|----------|------|------|--------------------|--|--|
| PARAMETER | SYMBOL | S1AL | S1BL | S1DL | S1GL | S1JL | S1KL | S1ML | UNIT | | |
| Marking code | | 1AL | 1BL | 1DL | 1GL | 1JL | 1KL | 1ML | | | |
| Maximum repetitive peak reverse voltage | V_{RRM} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V | | |
| Maximum RMS voltage | V_{RMS} | 35 | 70 | 140 | 280 | 420 | 560 | 700 | V | | |
| Maximum DC blocking voltage | V_{DC} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V | | |
| Maximum average forward rectified current | $I_{F(AV)}$ | 1 | | | | | | | A | | |
| Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load | I_{FSM} | 30 | | | | | | | A | | |
| Maximum instantaneous forward voltage (Note 1) @ 1 A | V_F | 1.1 | | | | | | | V | | |
| Maximum reverse current @ rated V_R $T_J=25^\circ\text{C}$ $T_J=125^\circ\text{C}$ | I_R | 5 50 | | | | | | | μA | | |
| Typical junction capacitance (Note 2) | C_J | 9 | | | | | | | pF | | |
| Typical reverse recovery time (Note 3) | t_{rr} | 1.8 | | | | | | | μs | | |
| Typical thermal resistance | $R_{\theta JL}$ $R_{\theta JA}$ | 25 85 | | | | 30 85 | | | $^\circ\text{C/W}$ | | |
| Operating junction temperature range | T_J | - 55 to +175 | | | | | | | $^\circ\text{C}$ | | |
| Storage temperature range | T_{STG} | - 55 to +175 | | | | | | | $^\circ\text{C}$ | | |

new datasheet version

| MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted) | | | | | | | | | | | |
|---|------------------------------------|--------------|------|------|------|----------|------|------|--------------------|--|--|
| PARAMETER | SYMBOL | S1AL | S1BL | S1DL | S1GL | S1JL | S1KL | S1ML | UNIT | | |
| Marking code | | 1AL | 1BL | 1DL | 1GL | 1JL | 1KL | 1ML | | | |
| Maximum repetitive peak reverse voltage | V_{RRM} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V | | |
| Maximum RMS voltage | V_{RMS} | 35 | 70 | 140 | 280 | 420 | 560 | 700 | V | | |
| Maximum DC blocking voltage | V_{DC} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V | | |
| Maximum average forward rectified current | $I_{F(AV)}$ | 1 | | | | | | | A | | |
| Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load | I_{FSM} | 30 | | | | | | | A | | |
| Maximum instantaneous forward voltage (Note 1) @ 1 A | V_F | 1.1 | | | | | | | V | | |
| Maximum reverse current @ rated V_R $T_J=25^\circ\text{C}$ $T_J=125^\circ\text{C}$ | I_R | 5 50 | | | | | | | μA | | |
| Typical junction capacitance (Note 2) | C_J | 9 | | | | | | | pF | | |
| Typical thermal resistance | $R_{\theta JL}$ $R_{\theta JA}$ | 25 85 | | | | 30 85 | | | $^\circ\text{C/W}$ | | |
| Operating junction temperature range | T_J | - 55 to +175 | | | | | | | $^\circ\text{C}$ | | |
| Storage temperature range | T_{STG} | - 55 to +175 | | | | | | | $^\circ\text{C}$ | | |