

	Affected PN	Replacement PN	Product name	Rated voltage(V)	Rated capacitance(μF)	Case size(mm)		Specifications			
						ΦD	L	Ripple current ※1 (mA ms)	ESR ※2 (mΩ max.)	tanδ※3	LC ※4 (μA)
EOL	25SVPG15M			25	15	5	4.4	2800	30	0.12	75
		25SVPK33M	Conductive Polymer Aluminum Solid Capacitors	25	33	5	5.9	820	35	0.12	165
EOL	35SVPD8R2M			35	8.2	8	6.9	400	70	0.1	57
		35SVT39M	Conductive Polymer Aluminum Solid Capacitors	35	39	8	6.9	880	30	0.12	273
EOL	100SXE15MX			100	15	10	8	630	60	0.12	75
		100SXV18M	Conductive Polymer Aluminum Solid Capacitors	100	18	10	12.6	3000	30	0.12	90
EOL	63SXE39MX			63	39	10	8	690	50	0.12	122
		80SXV47M	Conductive Polymer Aluminum Solid Capacitors	80	47	10	12.6	3100	28	0.12	188
EOL	80SXE27MX			80	27	10	8	660	55	0.12	108
		80SXV47M	Conductive Polymer Aluminum Solid Capacitors	80	47	10	12.6	3100	28	0.12	188

Please contact us for detailed specifications.