

	Affected PN	Replacement PN	Product name	Rated voltage(V)	Rated temp. (°C)	Category voltage (°C)	Rated capacitance(μF)	Case size(mm)			ESR ※1 (mΩ max.)	tanδ※2	LC ※3 (μA)	Min.Packing Qty(pcs)
								L	W	H				
EOL	ETPF470M5H			2.5	105	105	470	7.3	4.3	3.8	5	0.10	117.5	2000
		2R5TPE470M7	Conductive Polymer Tantalum Solid Capacitors	2.5	105	105	470	7.3	4.3	1.8	7	0.10	117.5	3000
EOL	6TPE330MAA			6.3	85	105	330	7.3	4.3	3.8	10	0.10	207.9	2000
		6TPF330M9L	Conductive Polymer Tantalum Solid Capacitors	6.3	105	105	330	7.3	4.3	2.8	9	0.10	207.9	2500
EOL	10TPE68M			10	105	105	68	7.3	4.3	1.8	25	0.10	68.0	3000
		10TPC100M	Conductive Polymer Tantalum Solid Capacitors	10	105	105	100	7.3	4.3	1.9	45	0.10	100.0	3000
EOL	4TPB330ML			4	105	105	330	7.3	4.3	2.8	40	0.10	132.0	2500
		4TPE330M	Conductive Polymer Tantalum Solid Capacitors	4	105	105	330	7.3	4.3	1.8	25	0.10	132.0	3000
EOL	6TPB220ML			6.3	105	105	220	7.3	4.3	2.8	40	0.10	138.6	2500
		6TPE220M	Conductive Polymer Tantalum Solid Capacitors	6.3	105	105	220	7.3	4.3	1.8	25	0.10	138.6	3000
EOL	10TPC68M			10	105	105	68	7.3	4.3	1.9	45	0.10	68.0	3000
		10TPC100M	Conductive Polymer Tantalum Solid Capacitors	10	105	105	100	7.3	4.3	1.9	45	0.10	100.0	3000
EOL	25TQC22MYFT			25	105	105	22	7.3	4.3	1.4	70	0.10	55.0	3000
		25TQC22MD2	Conductive Polymer Tantalum Solid Capacitors	25	105	105	22	7.3	4.3	1.9	60	0.10	55.0	3000

Please contact us for detailed specifications.